

CMS-F (Selective) Profile Nipple

The CMS-F (SELECTIVE) Profile Nipple is a TOP NO-GO Nipple that provides for the location of various wireline flow control devices in the production string.

SIZE INCHES / mm	OD INCHES / mm	SEAL BORE INCHES / mm
2.375 / 60,33	2.56 / 65,07	1.812 / 46,02
		1.875 / 47,63
2.875 / 73,03	3.030 / 76,96	2.125 / 53,98
		2.188 / 55,58
		2.252 / 57,20
		2.312 / 58,72
3.500 / 88,90	3.687 / 95,22	2.562 / 65,07
		2.750 / 69,85
		2.812 / 71,42
4.500 / 96,77	5.2 / 132,08	3.688 / 93,67
		3.75 / 95,25
		3.813 / 96,85



CMS-R (Non-selective) Profile Nipple

The CMS-R (NON-SELECTIVE) Profile Nipple is a Bottom NO-GO Nipple that provides for the location of various wireline flow control devices in the production string.

SIZE INCHES / mm	OD INCHES / mm	SEAL BORE INCHES / mm	NO-GO ID INCHES / mm
2.375 / 60,33	3.030 / 76,96	1.781 / 45,24"	1.728 / 43,89
		1.812 / 46,02	1.76 / 44,70
		1.875 / 47,63	1.822 / 46,28
2.875 / 73,03	3.668 / 93,17	2.125 / 53,97	2.075 / 52,70
		2.250 / 57,15	2.197 / 55,80
		2.312 / 58,72	2.205 / 56,01
3.500 / 88,90	4.500 / 114,30	2.562 / 65,07	2.443 / 62,05
		2.750 / 69,85	2.635 / 66,85
		2.812 / 71,42	2.666 / 67,72
4.500 / 96,77	4.920 / 124,97	3.813 / 96,85	3.725 / 124,97

