

CMS-6 Anchor Packer

The CMS-6 Anchor Packer is a single grip compression packer designed for use as the bottom packer in a zonal isolation completion. It is typically used in conjunction with a CMS-5 anchor packer to provide a two-packer system which can be set by compression. This combination in conjunction with a T-2 On/Off Tool allows for zonal isolation while providing the facility to retrieve the tubing if required without disturbing the packers. It is set by applying a quarter turn at the packer and setting down weight and is released by straight pick up. It has an extended seal area which allows tubing movement and/or pressure changes between the packers. It can also be used as a single grip production packer in applications where low differential pressures from below are anticipated.

Features and Benefits

- Extended stroke seal area maintains a seal in all conditions.
- Large bypass area
- Available in RH Auto or LH Auto or manual J-Slot configurations
- Sets with compression and retrieves with straight pull
- Can be used as a single string production packer in suitable conditions

Applications

- Zone Isolation
- Frac stimulation
- Cementing
- Production

SIZE INCHES / mm	WEIGHT LBS/FT / kg/m	MAX OD INCHES / mm	MIN ID INCHES / mm	STANDARD THREAD CONNECTIONS
4.500 / 114,30	9.5 - 13.5 / 14,1 - 20,1	3.750 / 95,25	1.925 / 48,90	2.375 EU 8RD
5.000 / 127,00	14.0 - 20.0 / 20,8 - 29,8	4.125 / 104,78	1.925 / 48,90	2.375 EU 8RD
	20.0 - 23.0 / 29,8 - 29,8	4.500 / 114,30	1.985 / 50,42	2.375 EU 8RD
5.500 / 139,70	14.0 - 20.0 / 20,8 - 29,8	4.625 / 117,48	1.985 / 50,42	2.375 EU 8RD
	20.0 - 23.0 / 29,8 - 34,2	4.500 / 114,30	2.360 / 59,94	2.875 EU 8RD
	15.5 - 20.0 / 23,1 - 29,8	4.625 / 117,48	2.360 / 59,94	2.875 EU 8RD
6.625 / 1682,8	24.0 - 32.0 / 35,7 - 47,6	5.500 / 139,70	2.484 / 63,09	2.875 EU 8RD
	17.0 - 24.0 / 25,3 - 35,7	5.750 / 146,05	2.484 / 63,09	2.875 EU 8RD
7.000 / 177,80	17.0-26.0 / 25,3 - 38,7	6.000 / 152,40	2.485 / 63,12	2.875 EU 8RD

